## **K**NEXGO

# KD69

### **Card Payment Speaker**

The KD69 series is a mini and versatile card payment speaker designed for all types of merchants, from SMEs to chain stores. Featuring an integrated speaker and card reader, it supports QR, EMV, NFC, and mobile payments. With dual-color screens, real-time confirmation, robust security (PCI & EMV), and extended battery life, it ensures seamless, fraud-resistant transactions across various usage scenarios worldwide.

#### **Features**

- All-in-One Integration of Speaker and POS
- Real-Time
  Visual and Auditory Notifications
  Provide Instant Confirmation
- Security
  PCI 6.2 Certified Highest Security
  Standards







AN&TAP TO PAY

VISA

## KD69 Card Payment Speaker



Speaker+NFC+PIN+IC (Standard) Speaker (Optional) Speaker+NFC (Optional)

#### **Specifications**

|                     | KD69  | KD69R   | KD69P          |
|---------------------|---|---|----------------|
| OS                  | RTOS  |   |                |
| Processor           | ARM Cortex-A5   |   |                |
| Secure<br>Processor | None  | ARM Cortex-M4   |                |
| Memory              | RAM 8MB+Flash 12MB Support flash extend up to 64MB  |   |                |
| NFC<br>Contactless  | None  | EMV Contactless NFC Tag   |                |
| IC Contact          | None  | None  | EMV Chip & PIN |
| LED Indicator       | 1*RGB LED, Power and Status indicator   |   |                |
| Rear LCD            | 2.3", Color Screen, 284*76  |   |                |
| Front LCD           | 2.8", Color Screen, 320*240   | 2.8", Color Screen, 320*240(DQR)<br>2.3", Color Screen, 284*76(SQR)   |                |
| Ports               | 1*Micro SIM, USB Type C   |   |                |
| Battery             | 3.7V/2600mAh  |   |                |
| Com.                | 4G Cat1, Wi-Fi(Optional)  |   |                |
| Keypad              | 5*Keys(PWK, Vol±, FN, Reset) Physical keypad(0~9+5*FNs)   |   |                |
| Audio               | Speaker 4Ω&3W   |   |                |
| Power               | DC5.0V/1.0A   |   |                |
| Environmental       | Operating Temperature: -10°C to 50°C<br>Storage Temperature: -20°C to 60°C<br>Relative Humidity : 5% to 95%(Non-Condensing) |   |                |
| Certifications      | CE, FCC, RoHS   | PCI PTS 6.x&7, EMV L1&L2, EMV CL L1,<br>Mastercard Paypass, Visa Paywave, JCB J/Speedy,<br>Amex Expresspay, Discover D-PAS, UnionPay QuickPass,<br>RuPay, MCCS, Mastercard TQM, FCC, CE, BIS, WPC, RoHS |                |
| Dimensions          | 103.8mm L×88.1mm W×153.2mm H  |   |                |
| Weight              | 257g  | 274g  | 278g           |

E : Sales@xgd.com W : www.nexgoglobal.com