NEXGO

UN10

The UN10 is engineered for ultimate flexibility and efficiency. Powered by a high-performance Qualcomm chipset and Android 14, it delivers fast, secure, and stable operations. While its rugged, compact design guarantees reliability in demanding environments, its versatile connectivity and multi-payment support ensure seamless integration into any self-service scenario.



Features

Compact and Flexible
Compact size with multiple mounting brackets for easy integration.

Highly Reliable
Rugged, waterproof, dustproof and impact-resistant, stable and reliable in all harsh outdoor weather.

Smart and Secure
Excellent performance and user experience, compliant with PCI 7.X.

Android 14 | IK09/IK10 | IP66&IP65 | Proximity Sensor | Ambient Light Sensor

E : Sales@xgd.com **W** : www.nexgoglobal.com
A : 8th Floor, Jialian Payment Building, Science and Technology South 12th Road No. 20, Nanshan District, Shenzhen, Guangdong, China

UN10



Contactless/NFC



IC Cards



Merchant-presented QR code payment



Customer-presented QR code payment

Specifications

Model	UN10	UN10P	UN10R	UN10RS
OS	Android 14			
Processor	Qualcomm Quad-core Cortex-A53, 2.0GHz			
Display	3.5" HVGA (320 × 480) Color LCD, Capacitive Touch		2.36" (76 × 284) Color LCD	
Memory	2GB RAM + 16GB ROM			
Communication	4G/3G/2G + WiFi 2.4GHz/5GHz,802.11 a/b/g/n/ac + BT5.0 (Optional： Ethernet 10/100)			
Positioning	GPS, GLONASS, Galileo, BeiDou			
Card Readers	Contactless Cards	Chip Cards + Contactless Cards	Contactless Cards	Contactless Cards
Card Slots	1 × SIM + 2 × SAM (Optional: 1 × SIM + 2 × SAM + eSIM) (Optional: 1 × SIM + 4 × SAM)			1 × SIM + eSIM (Optional: 1 ×SAM + eSIM)
Camera	Front: 2 MP, FF		No	No
Audio	1×Microphone, 1×Speaker, 1×Audio Jack			
Sensor	Ambient Light Sensor, Infrared Sensor			
Ports	1 x USB Type-C (Slave), 1 x USB Type-A (Host), 1 x MDB Slave,1 x RS232(RJ45), 1 x Digital I/O, 1 x LAN(RJ45), 1x DC Power Port			1 x USB Type-C (Slave), 1 x MDB Slave, 1 x LAN(RJ45), 1 x DC Power Port
Protection Ratings	IP66 / IK10	IP65 / IK10	IP66 / IK09	
Power supply	DC 5V/3A Via USB-C or DC Power Port, DC 7V-48V Via MDB			
Physical	75.8mm (L) × 121.8mm (W) × 48mm (H)			75.8mm (L) x 121.8mm (W) x 24mm (H)
Accessories	Mounting Bracket, External 4G Antenna (Optional： Power Adapter)			
Certifications	PCI 7.x, EMV L1, EMV CL1,Quickpass, Paypass, Paywave, TQM, JCB, Discover, AMEX, IP66, IK10, CE, FCC, RoHS			
Environmental	Operating Temperature : -20°C to 70°C Storage Temperature : -30°C to 80°C Relative Humidity : 5% to 95%(Non-Condensing)		Operating Temperature : -20°C to 60°C Storage Temperature : -30°C to 80°C Relative Humidity : 5% to 95%(Non-Condensing)	

E : Sales@xgd.com **W** : www.nexgoglobal.com
A : 8th Floor, Jialian Payment Building, Science and Technology South 12th Road No. 20, Nanshan District, Shenzhen, Guangdong, China